



# DosDelete

This call removes a directory entry associated with a file name.

## Syntax

DosDelete (FileName, Reserved)

## Parameters

;FileName (PSZ) - input : Address of the name of the file to be deleted. :DosQSysInfo is called by an application during initialization to determine the maximum path length allowed by OS/2. ; Reserved (ULONG) - input : Reserved and must be set to zero.

## Return Code

rc (USHORT) - return Return code descriptions are: \* 0 NO\_ERROR \* 2 ERROR\_FILE\_NOT\_FOUND \* 3 ERROR\_PATH\_NOT\_FOUND \* 5 ERROR\_ACCESS\_DENIED \* 26 ERROR\_NOT\_DOS\_DISK \* 32 ERROR\_SHARING\_VIOLATION \* 36 ERROR\_SHARING\_BUFFER\_EXCEEDED \* 87 ERROR\_INVALID\_PARAMETER \* 206 ERROR\_FILENAME\_EXCED\_RANGE

## Remarks

Global file name characters are not permitted.

A file whose read-only attribute is set cannot be deleted. To change the setting of the read-only bit, call DosSetFileMode.

## Example Code

## C Binding

```
<PRE> #define INCL_DOSFILEMGR
```

```
USHORT rc = DosDelete(FileName, Reserved);
```

```
PSZ FileName; /* File name path */ ULONG 0; /* Reserved (must be zero) */
```

```
USHORT rc; /* return code */ </PRE> This example deletes a file in the current directory named
```

test.dat.

```
<PRE> #define INCL_DOSFILEMGR

#define FILE_DELETE "test.dat" #define RESERVED 0L

USHORT rc;

rc = DosDelete(FILE_DELETE, /* File path name */
               RESERVED); /* Reserved (must be zero) */

</PRE>
```

### MASM Binding

```
<PRE> EXTRN DosDelete:FAR INCL_DOSFILEMGR EQU 1

PUSH@ ASCIIZ FileName ;Filename path name string PUSH DWORD 0 ;Reserved (must be zero) CALL
DosDelete

Returns WORD </PRE>
```

## Note

Text based on [http://www.edm2.com/index.php/DosDelete\\_\(FAPI\)](http://www.edm2.com/index.php/DosDelete_(FAPI))

Family API		
DOS	Process Manager	DosBeep DosExit DosSleep DosExecPgm
	File Manager	DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSetFileMode DosOpen DosQFileInfo DosRead DosQFileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSinfo DosShutdown
	Memory Manager	DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias
	NLS	DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage
	Date and Time	DosSetDateTime DosGetDateTime
	Devices	DosDevConfig DosDevIOct1 DosDevIOct12
	Signals	DosHoldSignal DosSetSigHandler
	Misc	BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec
KBD		KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek

<b>Family API</b>	
VIO	<a href="#">VioGetBuf</a> <a href="#">VioGetConfig</a> <a href="#">VioGetCurPos</a> <a href="#">VioGetCurType</a> <a href="#">VioGetPhysBuf</a> <a href="#">VioReadCellStr</a> <a href="#">VioReadCharStr</a> <a href="#">VioScrollUp</a> <a href="#">VioScrollDn</a> <a href="#">VioScrollLf</a> <a href="#">VioScrollRt</a> <a href="#">VioScrUnLock</a> <a href="#">VioSetCurPos</a> <a href="#">VioSetCurType</a> <a href="#">VioSetMode</a> <a href="#">VioGetMode</a> <a href="#">VioShowBuf</a> <a href="#">VioWrtCellStr</a> <a href="#">VioWrtCharStr</a> <a href="#">VioWrtCharStrAtt</a> <a href="#">VioWrtNAttr</a> <a href="#">VioWrtNCell</a> <a href="#">VioWrtNChar</a> <a href="#">VioWrtTTY</a> <a href="#">VioScrLock</a> <a href="#">VioPopUp</a>
Tools	<a href="#">BIND</a>
Modules	<a href="#">DOSCALLS.DLL</a> <a href="#">VIOCALLS.DLL</a> <a href="#">KBDCALLS.DLL</a> <a href="#">MSG.DLL</a>
Libraries	<a href="#">API.LIB</a> <a href="#">OS2386.LIB</a> <a href="#">FAPI.LIB</a> <a href="#">DOSCALLS.LIB</a> <a href="#">SUBCALLS.LIB</a>

2018/08/25 15:05 · [prokushev](#) · [0 Comments](#)

From:  
<http://osfree.ru/doku/> - **osFree wiki**

Permanent link:  
<http://osfree.ru/doku/doku.php?id=en:docs:fapi:dosdelete&rev=1535294042>

Last update: **2018/08/26 14:34**

