



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

KbdGetCp

This call allows a process to query the code page being used to translate scan codes to ASCII characters.

Syntax

```
KbdGetCp (Reserved, CodePageID, KbdHandle)
```

Parameters

- Reserved (ULONG) - input: Reserved and must be set to zero.
- CodePageID (USHORT) - output: Address of the code page ID located in the application's data area. The keyboard support copies the current code page ID for a specified keyboard handle into this word. The code page ID is equivalent to one of the code page IDs specified in the CONFIG.SYS CODEPAGE = statement or 0000.
- KbdHandle (HKBD) - input: Default keyboard or the logical keyboard.

Return Code

rc (USHORT) - return: Return code descriptions are:

- 0 NO_ERROR
- 373 ERROR_KBD_PARAMETER
- 439 ERROR_KBD_INVALID_HANDLE
- 445 ERROR_KBD_FOCUS_REQUIRED
- 447 ERROR_KBD_KEYBOARD_BUSY
- 464 ERROR_KBD_DETACHED
- 504 ERROR_KBD_EXTENDED_SG

Remarks

The CodePageID is the currently active keyboard code page. A value of 0 indicates the code page

translation table in use is the ROM code page translation table provided by the hardware.

Bindings

C

```
#define INCL_KBD

USHORT rc = KbdGetCp(Reserved, CodePageID, KbdHandle);

ULONG Reserved; /* Reserved (must be zero) */
PUSHORT CodePageID; /* Code Page ID */
HKBD KbdHandle; /* Keyboard handle */

USHORT rc; /* return code */
```

MASM

```
EXTRN KbdGetCp:FAR
INCL_KBD EQU 1

PUSH DWORD Reserved ;Reserved (must be zero)
PUSH@ WORD CodePageID ;Code Page ID
PUSH WORD KbdHandle ;Keyboard handle
CALL KbdGetCp

Returns WORD
```

From:

<http://osfree.ru/doku/> - **osFree wiki**

Permanent link:

<http://osfree.ru/doku/doku.php?id=en:docs:fapi:kbdgetcp&rev=1634999709>

Last update: **2021/10/23 14:35**

