



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

MouFlushQue

This call directs the mouse driver to flush (empty) the mouse event queue and the monitor chain data for the session.

Syntax

```
MouFlushQue (DeviceHandle)
```

Parameters

- DeviceHandle (HMOU) - input : Mouse device handle from a previous MouOpen.

Return Code

rc (USHORT) - return:Return code descriptions are:

- 0 NO_ERROR
- 385 ERROR_MOUSE_NO_DEVICE
- 466 ERROR_MOU_DETACHED
- 501 ERROR_MOUSE_NO_CONSOLE
- 505 ERROR_MOU_EXTENDED_SG

Bindings

C

```
#define INCL_MOUSE  
  
USHORT rc = MouFlushQue(DeviceHandle);  
  
HMOU DeviceHandle; /* Mouse device handle */
```

```
USHORT rc;          /* return code */
```

MASM

```
EXTRN MouFlushQue:FAR
INCL_MOU EQU 1

PUSH WORD DeviceHandle ;Mouse device handle
CALL MouFlushQue

Returns WORD
```

From:
<http://osfree.ru/doku/> - osFree wiki

Permanent link:
<http://osfree.ru/doku/doku.php?id=en:docs:fapi:mouflushque&rev=1634203731>

Last update: **2021/10/14 09:28**

