 This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · 0 Comments
2021/08/20 03:18 · prokushev · 0 Comments

MouClose

MouClose closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

Syntax

```
MouClose (DeviceHandle)
```

Parameters

- DeviceHandle (HMOU) - input : Mouse device handle from a previous MouOpen.

Return Code

rc (USHORT) - return:Return code descriptions are:

- 0 - NO_ERROR
- 385 - ERROR_MOUSE_NO_DEVICE
- 466 - ERROR_MOU_DETACHED
- 501 - ERROR_MOUSE_NO_CONSOLE
- 505 - ERROR_MOU_EXTENDED_SG

Bindings

C

```
#define INCL_MOU

USHORT  rc = MouClose(DeviceHandle);

HMOU    DeviceHandle;  /* Mouse device handle */
```

```
USHORT  rc;             /* return code */
```

MASM

```
EXTRN  MouClose:FAR
INCL_MOU            EQU 1

PUSH   WORD    DeviceHandle  ;Mouse device handle
CALL   MouClose

Returns WORD
```

From:
https://osfree.ru/doku/ - **osFree wiki**

Permanent link:
https://osfree.ru/doku/doku.php?id=en:docs:fapi:mouclose&rev=1634264884

Last update: **2021/10/15 02:28**