KbdFreeFocus

Bindings: C, MASM

This call frees the logical-to-physical keyboard bond created by *KbdGetFocus*.

KbdFreeFocus (KbdHandle)

KbdHandle (**HKBD**) - input Default keyboard or the logical keyboard.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
439	ERROR_KBD_INVALID_HANDLE
445	ERROR_KBD_FOCUS_REQUIRED
464	ERROR_KBD_DETACHED
504	ERROR_KBD_EXTENDED_SG

Remarks

KbdFreeFocus may be replaced by issuing *KbdRegister*. Unlike other keyboard subsystem functions, the replaced *KbdFreeFocus* is called only if there is an outstanding focus.

C bindings

```
#define INCL_KBD

USHORT  rc = KbdFreeFocus(KbdHandle);

HKBD             KbdHandle;     /* Keyboard handle */

USHORT           rc;            /* return code */
```

MASM bindings

```
EXTRN  KbdFreeFocus:FAR
INCL_KBD            EQU 1

PUSH   WORD    KbdHandle     ;Keyboard handle
CALL   KbdFreeFocus

Returns WORD
```

From:
https://osfree.org/doku/ - **osFree wiki**

Permanent link:
https://osfree.org/doku/doku.php?id=en:ibm:prcp:kbd:freefocus

Last update: **2016/09/15 02:32**