

MouClose

Bindings: C, MASM

This call closes the mouse device for the current session.

MouClose (**DeviceHandle**)

DeviceHandle (**HMOU**) - input Mouse device handle from a previous *MouOpen*.

rc (**USHORT**) - return Return code descriptions are:

| | |
|----------|------------------------|
| 0 | NO_ERROR |
| 385 | ERROR_MOUSE_NO_DEVICE |
| 466 | ERROR_MOU_DETACHED |
| 501 | ERROR_MOUSE_NO_CONSOLE |
| 505 | ERROR_MOU_EXTENDED_SG |

Remarks

MouClose closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

C bindings

```
#define INCL_MOU

USHORT rc = MouClose(DeviceHandle);

HMOU      DeviceHandle; /* Mouse device handle */

USHORT    rc;           /* return code */
```

MASM bindings

```
EXTRN MouClose:FAR
INCL_MOU EQU 1

PUSH WORD DeviceHandle ;Mouse device handle
CALL MouClose

Returns WORD
```

From:

<https://osfree.ru/doku/> - **osFree wiki**

Permanent link:

<https://osfree.ru/doku/doku.php?id=en:ibm:prcp:mou:close>

Last update: **2016/09/15 03:13**

