MouDeRegister

Bindings: C, MASM

This call deregisters a mouse subsystem previously registered within a session.

MouDeRegister ( )

rc (**USHORT**) - return Return code descriptions are:

0	**NO_ERROR**
385	ERROR_MOUSE_NO_DEVICE
416	ERROR_MOUSE_DEREGISTER
466	ERROR_MOU_DETACHED
505	ERROR_MOU_EXTENDED_SG

Remarks

Processes issuing MouDeRegister calls must conform to the following rules:

- The process that issued the MouRegister must release the session (by a MouDeRegister) from the registered subsystem before another **PID** may issue MouRegister.
- The process that issued the MouRegister is the only process that may issue MouDeRegister against the currently registered subsystem.
- After the owning process has released the subsystem with a MouDeRegister, any other process in the session may issue a MouRegister and therefore modify the mouse support for the entire session.

C bindings

```
#define INCL_MOU

USHORT  rc = MouDeRegister(VOID);

USHORT          rc;             /* return code */
```

MASM bindings

```
EXTRN  MouDeRegister:FAR
INCL_MOU            EQU 1

CALL   MouDeRegister

Returns WORD
```

From:
https://osfree.ru/doku/ - **osFree wiki**

Permanent link:
https://osfree.ru/doku/doku.php?id=en:ibm:prcp:mou:dereg

Last update: **2016/09/15 03:31**