VioGetCurPos

Bindings: C, MASM

This call returns the coordinates of the cursor.

VioGetCurPos (Row, Column, VioHandle)

Row (**PUSHORT**) - output Address of the current Row position of the cursor where 0 is the top row.

Column (**PUSHORT**) - output Address of the current column position of the cursor where 0 is the leftmost column.

VioHandle (**HVIO**) - input This must be zero unless the caller is a Presentation Manager application, in which case it must be the value returned by VioGetPs.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
355	ERROR_VIO_MODE
436	ERROR_VIO_INVALID_HANDLE
465	ERROR_VIO_DETACHED

C bindings

```
#define INCL_VIO

USHORT  rc = VioGetCurPos(Row, Column, VioHandle);

PUSHORT          Row;           /* Row return data */
PUSHORT          Column;        /* Column return data */
HVIO             VioHandle;     /* Vio handle */

USHORT           rc;            /* return code */
```

MASM bindings

```
EXTRN  VioGetCurPos:FAR
INCL_VIO            EQU 1

PUSH@  WORD     Row           ;Row return data
PUSH@  WORD     Column        ;Column return data
PUSH   WORD     VioHandle     ;Vio handle
CALL   VioGetCurPos

Returns WORD
```

From:
https://ftp.osfree.org/doku/ - **osFree wiki**

Permanent link:
https://ftp.osfree.org/doku/doku.php?id=en:ibm:prcp:vio:getcurpos

Last update: **2016/09/15 05:03**